

All the facts at a glance



Power unit		Under
Engine	4-cylinder diesel engine, liquid-cooled	Front v
Manufacturer	Cummins	Tyre eq
Туре	QSB4.5 C155	Tyre siz
Output		Rear w
Nominal	116kW at 2,000rpm (according to DIN)	Tyre siz
ECO mode	106kW at 1,700rpm	Drive
Exhaust emissions		Standa
standard	EU Stage 3a, US EPA Tier 3	Option
Fuel tank	215 litres	
		Speeds
		Paving
		Travel
		Outsid
		Mater
		Норре
		Width
		Feed h
		Push-r
		Positio

Undercarriage		
Front wheels	4, mounted on bogies (oscillating axle)	
Tyre equipment	elastic solid rubber tyres	
Tyre size	540/300 – 390mm	
Rear wheels	2, pneumatic tyres, tubeless	
Tyre size	14.00 R 25	
Drive	separate hydraulic drive provided for each wheel	
Standard	2 rear wheels (6x2)	
Option	2 rear wheels and 2 front wheels (6x4)	
	2 rear wheels and 4 front wheels (6x6)	
Speeds		
Paving	up to 18m/min., infinitely variable	
Travel	up to 20km/h, infinitely variable	
Outside turning radius	minimum 3.5m (with Pivot Steer)	
Material hopper		
Hopper capacity	13t	
Width	3,265mm	
Feed height	594mm (bottom of material hopper)	
Push-rollers	oscillating	
Position	can be displaced forwards by 75mm or 150mm	



conveyors and au		Screed options		
Conveyors	2, with replaceable feeder bars,	AB 480	basic width	2.55r
	conveyor movement reversible for a short time		infinitely variable range	2.55m to 4.8r
Drive	separate hydraulic drive provided		maximum width	6.3r
	for each conveyor	AB 500	basic width	2.55r
peed	up to 33m/min., infinitely variable		infinitely variable range	2.55m to 5r
	(manual or automatic)		maximum width	7r
Augers	2, with replaceable auger blades,	Screed version	TV	
	auger rotation reversible	Layer thickness	up to 30cm	
Diameter	400mm	Screed heating	electric by heating rods	
Drive	separate hydraulic drive provided	Power supply	three-phase A.C. generator	
	for each auger			
peed	up to 84 rpm, infinitely variable	Dimensions (transport) and weight		
	(manual or automatic)	1 1		
Height	infinitely variable by 15cm, hydraulic,	Length	tractor unit with screed	
	lowest position 10cm above the ground	AB 480/500 TV	6.04m	
Lubrication	automatic centralized lubrication system with	Weight	tractor unit with screed	
	electrically driven grease pump	AB 500 TV	17.5t	

Key: AB = Extending Screed TV = with tamper and vibrators

