

All the facts at a glance



Power unit				
Engine	6-cylinder diesel engine, liquid-cooled			
Manufacturer	Cummins			
Туре	QSB6.7-C170			
Output				
Nominal	127kW at 2,000rpm (according to DIN)			
ECO mode	116kW at 1,700rpm			
Exhaust emissions				
standard	EU Stage 3a, US EPA Tier 3			
Fuel tank	220 litres			

Undercarriage	
Front wheels	4, mounted on bogies (oscillating axle)
Tyre equipment	solid tyres
Tyre size	540/300 - 390mm
Rear wheels	2, pneumatic tyres, tubeless
Tyre size	14.00 R 25
Drive	separate hydraulic drive provided for each wheel
Standard	2 rear wheels and 2 front wheels powered
Option	2 rear wheels and 4 front wheels powered
	(all-wheel drive)
Speeds	
Paving	up to 18m/min., infinitely variable
Travel	up to 20km/h, infinitely variable
Outside Turning Radius	3.5m (with Pivot Steer)

Material hopper	
Hopper capacity	13t
Width	3,265mm
Feed height	594mm (bottom of material hopper)
Push-rollers	oscillating
Position	can be adjusted lengthwise by 75mm or 150mm



Conveyors and augers		Screed options		
Conveyors	2, with replaceable feeder bars,	AB 500	basic width	2.55m
	conveyor movement reversible for a short time		infinitely variable range	2.55m to 5m
Drive	separate hydraulic drive provided		maximum width (TV/TP1)	8m
	for each conveyor	AB 600	basic width	3m
Speed	up to 33m/min., infinitely variable		infinitely variable range	3m to 6m
	(manual or automatic)		maximum width (TV)	8m
Augers	2, with replaceable auger blades,	Screed Versions	TV, TP1 (AB 500)	
	auger rotation reversible	Layer Thickness	up to 30cm	
Diameter	400mm	Screed Heating	electric by heating rods	
Drive	separate hydraulic drive provided	Power Supply	three-phase A.C. generator	
	for each auger			
Speed	up to 84rpm, infinitely variable (manual or automatic)	Dimensions (transport) and weights		
Height	infinitely variable by 15cm, hydraulic,	Length	tractor unit and screed	
5	lowest position 10cm above the ground	AB 500/AB 600	TV	6m
Lubrication	centralized lubrication system with electrically	AB 500	TP1	6.1m
	driven grease pump	Weights	tractor unit and screed	
		AB 500 TV	pave widths up to 5m	17.8t
			pave widths up to 8m	20.3t

 Key:
 AB = Extending Screed
 TV = with tamper and vibrators

 TP1 = with tamper and 1 pressure bar



Subject to technical modification.