

All the facts at a glance





Power unit		
Engine	6-cylinder diesel engine, liquid-cooled	
Manufacturer	Deutz	
Туре	TCD 2015 V06 4V	
Output		
Nominal	300kW at 1,800rpm (according to DIN)	
ECO mode	292kW at 1,500rpm	
Exhaust emissions		
standard	EU Stage 3a, US EPA Tier 3	
Fuel tank	600 litres	


Undercarriage		
Crawler tracks	provided with rubber pads	
Ground contact	3,300mm x 400mm	
Suspension	rigid	
Track tension adjuster	elastomer	
Track roller lubrication	lifetime	
Traction drive	hydraulic, separate drive and electronic control	
	provided for each crawler track	
Speeds		
Paving	up to 24m/min., infinitely variable	
Travel	up to 4.5km/h, infinitely variable	
Steering	by alteration of track running speeds	

Material hopper		
Hopper capacity	17.5t	
Width	3,885mm	
Feed height	620mm (centre of material hopper)	
Push-rollers	oscillating	
Position	can be displaced forwards by 100mm	

TV = with tamper and vibrators

TP1 = with tamper and 1 pressure bar **TP2 =** with tamper and 2 pressure bars

TVP2 = with tamper, vibrators and 2 pressure bars
TP2 Plus = with special tamper, 2 pressure bars and additional weights



Conveyors and augers			
Conveyors	2, with replaceable feeder bars,		
	conveyor movement reversible for a short time		
Drive	separate hydraulic drive provided		
	for each conveyor		
Speed	up to 43m/min., infinitely variable		
	(manual or automatic)		
Augers	2, with replaceable auger blades		
Diameter	420mm		
Drive	hydraulic, separate drive provided for		
	each auger		
Speed	up to 93rpm, infinitely variable		
Height	infinitely variable by 20cm, hydraulic		
Lubrication	centralized lubrication system		
	with electrically driven grease pump		

Screed options		
AB 600	basic width	3m
	infinitely variable range	3m to 6m
	maximum width (TV/TP1/TP2)	9.5m
SB 300	basic width	3m
	maximum width (TV)	16m
Screed versions	TV, TP1, TP2, TP2 Plus (AB 600), TVP2 (SB 300)	
Layer thickness	up to 50cm (SB 300)	
Screed heating	electric by heating rods	
Power supply	three-phase A.C. generator	

Dimensions (transport) and weights			
Length	tractor unit with screed		
AB 600	TV	7m	
	TP1/TP2/TP2 Plus	7.1m	
SB 300	TV/TP1/TP2/TVP2	6.9m	
Weights	tractor unit with screed		
AB 600 TV	pave widths up to 6m	28.7t	
	pave widths up to 9.5m	32.6t	

Subject to technical modification.