

### DF 4500 dust control system

The Dust Fighter **DF4500** is a dust control system with a maximum range of 30 metres, ideal for small and medium size working areas.

#### Notes

If you are powering the Dust-Fighter from a generating set we suggest you use a 8 kW – 380V generator, or larger

#### Standard Equipment

- Integrated control panel
- Electric tilting
- Phase inverter
- Booster pump with peripheral impeller
- Flowmeter for pump protection
- Pressure gauge for outlet pressure reading
- Stainless steel crown with nozzles
- Water drain system
- Low speed trailer
- 2 height adjustable rear stabilizers and 2 front stabilizers
- Manual rotation and tilting system

#### Optional

- Automatic rotation
- Dedicated colour (RAL)
- Remote control
- Ball or eyelet hitch
- Available without trailer



Picture shown may not reflect actual configuration.

DF 4500	Technical Data
Electrical engine power (fan)	4 kW
Coverage (*without wind)	20 – 30 m*
Electrical connection	Inlet Plug 3-phase – 32 A
Water connection	UNI 45 / STORZ / CAMLOCK
Min/Max inlet pressure	1 / 4 bar
Water consumption	22 l/min
Water inlet filter	170 micron
Work angle	330°
Tilting	-20° / +40°
Dimension with tow bar and wheels	1780 x 1165 x 1800 mm (L x W x H)
Dry weight	290 kg