



## **Hydro light tower**

The **Hydro light tower** is a model with vertical mast and hydraulic lifting system. It is powered by a power generator placed on its back. The operator can choose between 10 kVA or 22 kVA power generators provided by Generac Mobile<sup>®</sup>. The Hydro model can be considered as a "two-in-one" solution ideal for customers interested in having a mobile lighting tower that also boasts a powerful generator.

## **Power generators**

The Hydro is provided with an **power generator** of your choice (10 kVA suggested for the LED version or 22 kVA suggested for the MH version).

# **Hydraulic mast**

A vertical telescopic mast with an hydraulic lifting system and a maximum height of 8.5 meters.

#### Site-tow trailer

The Hydro is equipped as standard with a **low speed site-tow trailer** to be easily towed on building sites.

## **Lamp options**

**Choose the lamp type you prefer** between 4×1000 metal halide or the innovative 4x320W LED floodlights.



Picture shown may not reflect actual configuration.





Hydro LED	Technical Data
Minimum dimensions (L x W x H)	3820 x 1566 x 2536 mm
Maximum dimensions (L x W x H)	3820 x 1566 x 8500 mm
Dry weight	751 kg
Lifting system	Hydraulic
Mast rotation	340°
Lamps power	4 x 320 W
Lamps type	LED
Total lumen	188160 Lm
Illuminated area	4500 m <sup>2</sup>
Inlet plug (A/V/Hz)	16/380/50 — 16/400/60
Optional generator	10 kVA
Wind speed resistance	110 km/h
Optional power generator	GMN-10P
Available for	Europe
Engine	Perkins 403D-11G
Cylinders (q.ty)	3
Engine speed (50 Hz)	1500 rpm
Engine cooling	Liquid
Stand by power (LTP)	10 kVA / 400 V / 50 Hz
Prime power (PRP)	9 kVA / 400 V / 50 Hz
Running time (with only lamps ON)	70 h
Avg. sound pressure	66 dB(A) @ 7m
Tank capacity	68 I
Liquid containment (110%)	$\sqrt{}$
Optional power generator	GMB-10P
Available for	International
Engine	Perkins 403D-11G
Cylinders (q.ty)	3
Engine speed (50 Hz)	1500 rpm
Engine cooling	Liquid
Stand by power (LTP)	9 kVA / 400 V / 50* Hz
Prime power (PRP)	8,5 kVA / 400 V / 50* Hz
Running time (with only lamps ON)	53 h
Avg. sound pressure	66 dB(A) @ 7m
Tank capacity	51 I
Liquid containment (110%)	No
	*60 Hz available on request



Picture shown may not reflect actual configuration.